

# DEF Transfer Hose - Braided



## Product Specifications

### Application

DEF Transfer Hose - Braided has superior compounding which is specifically designed to convey Diesel Exhaust Fluid, a high-purity, aqueous urea solution. The braided construction is engineered to reduce kinking and twisting in reeling applications.

### Construction

#### > Tube

Specially formulated low-extraction EPDM, peroxide cured

#### > Cover

Black specially formulated EPDM

#### > Reinforcement

Two-braid textile

### Temperature Range

-40°F to 140°F (-40°C to 60°C)

### Packaging

100' lengths

### Branding

Continental ContiTech DEF Transfer Hose 1½' (38.1 mm) Made in USA

### Order Codes

532-019

## DEF Transfer Hose - Braided

SAP #	ID		Nom. OD		Max. WP		Weight	
	in.	mm	in.	mm	psi	MPa	lb./ft.	kg/m
20531743	1½	38.1	2.10	53.2	250	1.72	0.81	1.21

Hose design ratio (burst pressure) 4:1.

Air & Multipurpose  
General Purpose  
Heavy Duty  
Push-on

Chemical Transfer

Cleaning Equipment

### Food

Dry Transfer  
Liquid Transfer  
Washdown

Marine

### Material Handling

Abrasives  
Bulk Transfer  
Cement & Concrete

Mining

### Petroleum

Aircraft Fueling  
Dispensing  
Dock  
Rig Supply  
Transfer Discharge  
Transfer S&D

Specialty

Steam

Vacuum

### Water

Discharge  
Suction & Discharge  
Washdown  
Garden

Welding

Coupling Systems

Equipment

Appendix